
1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name LI-ION BATTERY PACK FOR USE WITH PULSA 800 GASTOOLS
Synonyms 018545 - PRODUCT CODE

1.2 Uses and uses advised against

Uses BATTERIES • LITHIUM ION BATTERY • RECHARGEABLE BATTERY

1.3 Details of the supplier of the product

Supplier name RAMSETREID NZ (A DIVISION OF ITW NEW ZEALAND)
Address 23-29 Poland Road, Glenfield, Auckland, 0627, NEW ZEALAND
Telephone 0800 88 22 12
Email sales@ramsetreid.co.nz
Website <http://www.reids.co.nz>

1.4 Emergency telephone numbers

Emergency 0800 734 607

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NON HAZARDOUS ACCORDING TO NZ ENVIRONMENTAL PROTECTION AUTHORITY CRITERIA

2.2 GHS Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

For the battery cell, chemical materials are stored in a hermetically sealed metal case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage. However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by misuse, the gas release vent will be operated. The battery cell case will be breached at the extreme. Hazardous materials may be released. Moreover, if heated strongly by the surrounding fire, acrid or harmful fume may be emitted.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
COBALT LITHIUM DIOXIDE	12190-79-3	235-362-0	25 to <50%
ALUMINIUM POWDER (STABILISED)	7429-90-5	231-072-3	10 to <25%
COPPER	7440-50-8	231-159-6	10 to <25%
CARBON	7440-44-0	231-153-3	2.5 to <10%
ETHYL ACETATE	141-78-6	205-500-4	2.5 to <10%
ETHYLENE CARBONATE	96-49-1	202-510-0	2.5 to <10%
GRAPHITE	7782-42-5	231-955-3	2.5 to <10%
LITHIUM HEXAFLUOROPHOSPHATE(1-)	21324-40-3	244-334-7	2.5 to <10%
METAL CASING	-	-	Not Available

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	Exposure is considered unlikely unless casing is damaged. Flush gently with running water. Seek medical attention if irritation develops.
Inhalation	Exposure is considered unlikely. Due to product form / nature of use, an inhalation hazard is not anticipated.
Skin	Exposure is considered unlikely unless casing is damaged. Gently flush affected areas with water. Seek medical attention if irritation develops.
Ingestion	For advice, contact the National Poisons Centre on 0800 764 766 (0800 POISON) or +643 479 7248 or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.
First aid facilities	Eye wash facilities should be available.

4.2 Most important symptoms and effects, both acute and delayed

Adverse effects not expected from this product. Exposure to battery contents may cause irritation and potential burns.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent. Do NOT use water. Prevent contamination of drains and waterways.

5.2 Special hazards arising from the substance or mixture

Contents react with water. May explode if exposed to high temperatures due to pressure build up in battery casing. Lithium may burn in a fire situation and may be ejected from the battery. Damaged cells may evolve toxic and flammable vapours. May evolve carbon oxides and hydrogen fluoride when heated to decomposition.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

4W

4 Dry Agent (water MUST NOT be allowed to come into contact with substance).

W Risk of violent reaction or explosion. Wear liquid-tight chemical protective clothing and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

If spilt, collect and reuse where possible. If battery is broken or damaged, absorb liquid with sand or similar. Contain spillage, then collect and place in suitable containers for disposal. CAUTION: Avoid exposure to contents.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Take measures to prevent exposure to electrostatic discharge. Keep away from naked flames.

7.2 Conditions for safe storage, including any incompatibilities

Store tightly sealed in a cool, dry, well ventilated area, removed from water, incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Avoid temperatures above 70°C.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Cobalt metal dust & fume, as Co	WES [NZ]	--	0.05	--	--
Copper (fume)	WES [NZ]	--	0.2	--	--
Copper and its inorganic compounds, as Cu	WES [Proposed]	--	0.01	--	--
Copper, dusts & mists (as Cu)	WES [NZ]	--	1	--	--
Ethyl acetate	WES [NZ]	200	720	--	--
Graphite, all forms except graphite fibres	WES [NZ]	--	3	--	--

Biological limits

Ingredient	Determinant	Sampling Time	BEI
COBALT LITHIUM DIOXIDE	Cobalt in urine	End of shift at end of workweek	15 µg/L

Reference: ACGIH Biological Exposure Indices

8.2 Exposure controls

Engineering controls No special precautions are normally required when handling this product.

PPE

- Eye / Face** Not required under normal conditions of use.
- Hands** Wear PVC or rubber gloves.
- Body** Not required under normal conditions of use.
- Respiratory** Not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	BATTERY
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE

9.1 Information on basic physical and chemical properties

Odour threshold NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Heat above 70°C or incinerate. Deform. Mutilate. Crush. Pierce. Disassemble. Recharge. Short circuit. Expose over a long period to humid conditions.

10.5 Incompatible materials

Battery contents are incompatible with water (evolving flammable gas), oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrogen fluoride when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity No specific acute toxicity data exists for this product. Batteries consist of a hermetically sealed metallic container containing a number of chemicals and materials of construction that may be hazardous upon release. Over exposure considered unlikely unless battery ruptures and contact with contents occurs. Contents may be harmful.

Information available for the ingredients:

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
COPPER	--	> 2000 mg/kg (rat)	--
CARBON	> 2,000 mg/kg (rat)	--	--
ETHYL ACETATE	4100 mg/kg (mouse)	--	1600 ppm/8hrs (rat)
ETHYLENE CARBONATE	10 g/kg (rat)	> 3 g/kg (rabbit)	--
LITHIUM HEXAFLUOROPHOSPHATE(1-)	> 50 - 300 mg/kg (rat)	--	--

Skin Not classified as a skin irritant unless the battery ruptures. Contact with contents may cause irritation, redness, dermatitis and possible burns with prolonged contact.

Eye Not classified as an eye irritant unless the battery ruptures. Contact with contents may cause irritation, redness and possible burns with prolonged contact.

Sensitisation Not classified as causing skin or respiratory sensitisation unless the battery ruptures. Sufficient data from human studies exists to warrant classification of cobalt as a dermal sensitiser via skin contact, and a respiratory sensitiser via inhalation.

Mutagenicity No evidence of mutagenic effects.

Carcinogenicity No evidence of carcinogenic effects. Cobalt and cobalt compounds are classified as possibly carcinogenic to humans (IARC Group 2B).

Reproductive No relevant or reliable studies were identified.

STOT - single exposure Not classified as causing organ damage from single exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures. Exposure to contents may cause respiratory irritation.

STOT - repeated exposure Not expected to cause organ effects from repeated exposure. Due to the product form and nature of use, exposure to internal contents is not anticipated unless the battery ruptures.

Aspiration Not relevant.

12. ECOLOGICAL INFORMATION

PRODUCT NAME LI-ION BATTERY PACK FOR USE WITH PULSA 800 GASTOOLS

12.1 Toxicity

This product may be hazardous to the environment if not properly used or disposed of. Do not let internal components enter the marine environment. Avoid release to waterways, wastewater or ground water.

12.2 Persistence and degradability

This product is not readily biodegradable.

12.3 Bioaccumulative potential

Limited information was available at the time of this review.

12.4 Mobility in soil

This product has low mobility in soil.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Reuse or recycle where possible. Return to manufacturer/supplier. Contact the EPA or the manufacturer for additional information.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD ACCORDING TO LAND TRANSPORT RULE: DANGEROUS GOODS 2005; NZS 5433:2012, UN, IMDG OR IATA



	LAND TRANSPORT (NZS 5433)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3481	3481	3481
14.2 Proper Shipping Name	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT
14.3 Transport hazard class	9A	9A	9A
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code 4W

EmS F-A, S-I

Other information This battery is packed in or with equipment, however UN number 3480 may also apply.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Approval code MANUFACTURED ARTICLE

Group standard Something for which its intended use is primarily to do with its physical shape, rather than its chemical composition.

Inventory listings **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**
All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CCID	Chemical Classification and Information Database (HSNO)
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
EPA	Environmental Protection Authority [New Zealand]
GHS	Globally Harmonized System
HSNO	Hazardous Substances and New Organisms
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
TLV	Threshold Limit Value
TWA	Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

PRODUCT NAME LI-ION BATTERY PACK FOR USE WITH PULSA 800 GASTOOLS

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmtglobal.com

[End of SDS]