

Gap Seal

Paintable Acrylic Gap Sealant

Sealants



Key Features

- Flexible
- Paintable
- Water clean up



Joint Movement

Typical Properties

Appearance	White, non-sag smooth thixotropic paste
Chemical Type	Water-based Acrylic
Service Temperature	-10°C to + 80°C
Application Temperature	+5°C to + 35°C
Tool Working Time	15 minutes at 20°C
Max. Joint Movement	± 5%
Max. Joint Width	50mm
Elongation at Break ASTM D412	400%
Cure Rate	2mm per 24 hour period
Cure Hardness	Shore D 50
Skinning Time	30 minutes @ 20°C
Paintable	Acrylic and Vinyl paints - 30 minutes at 20°C Oil based paints - 24 hours
Substrates	Plasterboard, MDF, Plywood, Ceramic Tiles, Laminated Plastics, Timber, Fibre cement, Concrete & Brick

Advantages

- Resists cracking - flexible
- Paintable
- User friendly - clean up with water
- User friendly - low odour
- Easy to use - sag resistant
- Low VOC

Properties

Flexibility	Low
Water Resistance	Low
Water Immersion	No
Heat Resistant	No
Fire Rated	No
Low VOC	Yes
Paintable	Yes
Water Clean Up	Yes
Exterior Use	No
UV Resistant	No

Recommended Applications

- Sealing gaps & cracks
 - Architraves
 - Skirting boards
 - Chart & pictures rails

Gap Seal				Related Items
Order No.	Pack Size	Order Qty	Colour	Caulking Gun
GPSLWHG450	300mL Cartridge	20	White	CAGU300