

# ANCHORING SOLUTIONS

	Mechanical Anchor	Performance	Material	Seismic	Fire Rated	Concrete	Cracked Concrete	Solid Stone	Solid Block	Solid Brick	Hollow Slab	Hollow Slab	Hollow Brick	Plasterboard	Aerated Concrete	Particleboard	Timber	Cement Sheet	
				Seismic	Fire Rated	Concrete	Cracked Concrete	Solid Stone	Solid Block	Solid Brick	Hollow Slab	Hollow Slab	Hollow Brick	Plasterboard	Aerated Concrete	Particleboard	Timber	Cement Sheet	
<b>HEAVY DUTY</b>	SpaTec™ Xtrem™ Safety Anchors		Zn SS	■	■	■	■	■											
	AnkaScrew™ Xtrem™ Safety Anchors		Zn	■	■	■	■	■	■	■	■	■	■						
	TruBolt™ Xtrem™ Stud Anchor		Zn	■	■	■	■	■											
	Trubolt™ Stud Anchors		Zn GAL			■		■											
	Trubolt™ Stud Anchors SS		SS		■	■	■	■											
	Boa™ Coil Expansion Anchors		Zn			■		■											
<b>MEDIUM DUTY</b>	WERCS AnkaScrew™		Zn GAL		■	■	■	■	■	■	■	■	■						
	Ankascrew™ Screw-in Anchors		Zn			■		■	■	■	■	■	■						
	Dynabolt™ Plus Hex Nut		Zn SS GAL			■		■	■	■	■	■	■						
	Dynabolt™ Plus Flat Head		Zn			■		■	■	■	■	■	■						
	Dynabolt™ Plus Set Lok		Zn			■		■	■	■	■	■	■						
	Dynabolt™ Plus Hook Bolt		Zn			■		■	■	■	■	■	■						
	Dynabolt™ Plus Eye Bolt		Zn			■		■	■	■	■	■	■						
	Dynaset™ Drop-in Anchors		Zn SS			■		■											
<b>LIGHT DUTY</b>	ShureDrive™ Drive Anchor		Zn SS			■		■	■	■	■	■	■						
	RamPlug™ Nylon Frame Anchor		NYLON			■		■	■	■	■	■	■		■				
	Nylon Anchor		NYLON			■		■	■	■									
	EasyDrive™ Anchor		NYLON Zn SS			■		■	■	■	■	■	■		■				
	Plastic Plugs		PLASTIC			■		■	■	■	■	■	■						
	Concrete Nails		STEEL			■		■	■										
	Hollow Wall Anchors		Zn												■		■	■	■
	WallMate™ Plasterboard Anchors		Zn NYLON												■	■			

	Chemical Anchor	Performance	Material	Seismic	Fire Rated	Concrete	Cracked Concrete	Multi Direction	Overhead	Damp Hole	Underwater	Drilled Hole	Cored Hole	Indicative Strength
				Seismic	Fire Rated	Concrete	Cracked Concrete	Multi Direction	Overhead	Damp Hole	Underwater	Drilled Hole	Cored Hole	Indicative Strength
<b>CHEMICALS</b>	EPCON C8 XTREM™		Epoxy	■	■	■	■	■	■	■	■	■	■	5
	EPCON C6 PLUS		Epoxy	■	■	■	■	■	■	■	■	■	■	5
	CHEMSET 801 Xtrem™ XC²		Vinyl Ester	■	■	■	■	■	■	■	■	■	■	4
	CHEMSET 101 PLUS		Polyester		■	■	■	■	■	■	■	■	■	3
	Ultrafix™ PLUS		Polyester		■	■	■	■	■	■	■	■	■	3
	CHEMSET Maxima™ Capsule		Acrylic			■	■	■	■	■	■	■	■	2

### Web Links



Keep up to date with Ramset™ on our socials



Suitable for use in seismic design according to ANZ Standards (eg AS/NZ 1170.4).	Has good resistance to cyclic and dynamic loading. Resists loosening under vibration.	Anchor has an effective pull-down feature, or is a stud anchor. It has the ability to clamp the fixture to the base material.	Fire rated in accordance with the applicable standard or independent assessment.	May be used close to edges (or another anchor) without risk of splitting the concrete.	Temporary or removable anchor.	AISI Grade 316 stainless steel, resistant to corrosive agents including chlorides and industrial pollutants.	Steel Hot Dipped Galvanised to AS/NZS 4680:2006 and AS/NZS 1214:2016. Minimum thickness 42 micron. For external applications.	Steel Zinc Plated Minimum thickness 5 micron. Recommended for internal applications only.	Corrosion resistant. Not recommended for direct exposure to sunlight.	Steel Mechanically Galvanised Minimum thickness 42 micron. For external applications.

Ramset™ New Zealand Sales, Orders and Enquiries 0800 726 738 www.ramset.co.nz

Important Disclaimer: Any engineering information or advice ("Information") provided by Ramset™ in this document is issued in accordance with a prescribed standard, published performance data or design software. It is the responsibility of the user to obtain its own independent engineering (or other) advice to assess the suitability of the Information for its own requirements. To the extent permitted by law, Ramset™ will not be liable to the recipient or any third party for any direct or indirect loss or liability arising out of, or in connection with, the Information.